



Model	ZT 4537S	ZT 6537S	ZT 7537S	ZT 9037S	ZT 12537S
BURGU ÇAPI / Screw Diameter	45	65 mm	75 mm	90 mm	125 mm
L/D	37 D	37 D	37 D	37 D	37 D
ANA MOTOR GÜCÜ / Main Motor Power	79 kW	158 kW	184 kW	262 kW	380 kW
TORK / Torque	2.300 Nm	6.000 Nm	9.000 Nm	16.000 Nm	38.000 Nm
BURGU DEVRİ / Screw Speed	320 (1/min)	225 (1/min)	185 (1/min)	150 (1/min)	100 (1/min)
ISITMA BÖLGE SAYISI / Heating Zones	5	5	6	6	6
SOĞUTMA BÖLGE SAYISI / Cooling Zones	6	6	7	7	7
KAPASİTE (Max.) / Output	250 Kg/h	425 Kg/h	600 Kg/h	750 Kg/h	1.200 Kg/h
ÇALIŞMA EKSENİ / Extrusion Height	1000 mm	1100 mm	1100 mm	1100 mm	1100 mm
UZUNLUK / Length	2850 mm	3950 mm	4460 mm	5150 mm	5150 mm
GENİŞLİK / Width	1000 mm	1220 mm	1300 mm	1350 mm	1350 mm
YÜKSEKLİK / High	1400	1550 mm	1550 mm	1550 mm	1550 mm
AĞIRLIK / Weight	2200 Kg	3000 Kg	3300 Kg	4500 Kg	6.000 Kg

